

## Specification Sheet

<b>D85</b>		
<b>Specifications / features.</b>	<b>Values / features</b>	<b>Notes / Comments.</b>
Nominal System Impedance	4 ohm	(Z-min 3.4 ohm)
Frequency Response	90-20K Hz	(average response in room +/- 3 dB)
Frequency Roll Off	70 Hz	(-9 dB 80 Hz near field)
Crossover Frequency	1.6K Hz	"Phase focused" (2nd order)
Tweeter	1 x 1,1" Dome	Coated silk dome / Low compression
Woofers	1 x 6.5"	Polypropylene Cone, Inverted Dust cap
Power Handling	130 watt	Long term IEC-268-5 (cycled input 77-20K Hz)
Power Handling	70 watt	Rated IEC-268-5 (constant input 77-20K Hz)
Recommended Amp Power	25-300 watt	Recommended Amp Power Min / Max
Sensitivity	91 dB	Average SPL 2.83 volt / 1mtr (on axis 200-10K Hz)
Max SPL Continued	109 dB	Sinewave 100-8000 Hz / THD < 10%
Max SPL Peak	115 dB	Sinewave 100-8000 Hz / THD < 10%
System Principle		Sealed enclosure
Connection	Terminal Gold plating	Push terminal 4mm Cable
Finish	Paint	Satin White, Silver Gray, High Gloss Black
Cabinet dimensions	H x W	11.81 x 9.45 inch / 300 x 240 mm
Cabinet depth	D	3.74 inch / 95 mm
Dimensions Grille	H x W x T	11.57 x 9.21 x 0.39 inch / 294 x 234 x 10 mm
Weight	Netto	10.8 lbs / 4.9 kg
Placement Options		Keyhole mounting, prepared for alternative brackets
VESA Wall mounting pattern	VESA	100 mm x 100 mm
Version 1.1 - Oct 2022		