

IW150		
Specifications.	Values	Notes / Comments.
Nominal system impedance	4 ohm	(Z-min 3.4 ohm)
Frequency response	80-20Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	(-9 dB 80 Hz near field)
Crossover frequency	1.6Khz	"Phase focused" (4thd/2nd order)
Tweeter	3 x 1,1" Dome	Coated silk dome / Low compression
Woofers	2 x 5.25"	Coated Glass Fibre
Power handling	180 watt	Long term IEC-268-5 (cycled input 77-20Khz)
Power handling	90 watt	Rated IEC-268-5 (constant input 77-20Khz)
Recommended amp power	25-400 watt	Recommended amp power Min / Max
Sensitivity	90dB	Average SPL 2.83 volt / 1mtr (on axis 200-10KHz)
Max SPL continued	100 dB	Sinew ave 100-8000 Hz / THD < 10%
Max SPL peak	108 dB	Sinew ave 100-8000 Hz / THD < 10%
System princip		Sealed enclosure
Connection	Terminal gold plating	Push terminal 4 mm cable
Finish	Paint	Black cabinet & front / white Grill
Cut out	H x W	13.03 x 11.33 inch / 331 x 288 mm
Cabinet dimensions	H x W	12.95 x 11.25 invh / 329 x 286 mm
Cabinet depth	D	3.74 inch / 93 mm
Dimensions grill	H x W x D	14.17 x 12.51 inch / 360 x 318 mm
Weight	Netto	18.8 lbs / 8.5 kg
	Version 1. Feb 2019	