

Kinta FX ILS

- Compatible with ILS (Integrated Lighting System) products for wireless control
- Compact multi-effect with a Kinta, laser, and SMD strobe
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Projects countless razor-sharp multicolor beams
- SMD strobes produce eye-catching strobe effects and chases
- Red and green laser casts hundreds of beams
- Easily control the unit from DMX, Master/Slave, IRC-6, or the digital display
- Save time running cables and extension cords by power linking multiple units

Specifications

- DMX Channels: 2 or 9
- DMX Connectors: 3-pin XLR
- Light Source (Kinta): 4 LEDs (1 red, 1 green, 1 blue, 1 white) 7.5 W, (2.4 A), 50,000 hours life expectancy
- Light Source (Strobe): 16 SMD LEDs (white) 5 W, (1.6 A) 50,000 hours life expectancy
- Light Source (Laser): 650 nm/100 mW (red) laser diode, 520 nm/30 mW (green) laser diode
- Strobe Rate: 0 to 20 Hz
- Coverage Angle: 118°
- Power Linking: 17 units @ 120 V; 33 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 25 W, 0.5 A @ 120 V, 60 Hz
- Power and Current: 24 W, 0.2 A @ 230 V, 50 Hz
- Weight: 3.8 lb (1.7 kg)
- Size: 7.4 x 10.3 x 7.4 in (187 x 261 x 187 mm)
- Optional Controllers: IRC6
- Classified per EN/IEC 60825-1:2014
- Complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 56, dated May 8, 2019
- Approvals: CE, FDA, RoHS, UKCA

