

Specification Sheet

X15+		
Specifications / features.	Values / features	Notes / Comments.
THX® Certification	YES	THX® Certification Class Dominus
Frequency Response	16-200 Hz	(Average Response in Room +/- 3 dB)
Frequency Roll Off - THX EQ	16 Hz	(-6 dB 20 Hz Nearfield)
Frequency Roll Off - Anechoic EQ	16 Hz	(-6 dB 20 Hz Nearfield)
Variable Low Pass Filter	40-125 Hz	Continuously Variable / 4th Order
Low Pass Filter Bypass	40-200 Hz	No Low Pass
Fixed 80 Hz Filter	Yes	(Equivalent to THX 80Hz Ref Low Pass)
Phase Control	0 - 180 deg	Continuously Variable
Line level input/output	2 x RCA phono	Left / Right - input / output
Line level input/output	2 x XLR	Left / Right - Input / output
Amplifier type		Analog input / switch mode power output
Drive unit	2 x 15"	Extra Long Throw
System Principle	Push Pull	Sealed enclosure
Amplifier Power output RMS	700 watt	<0.5% THD at 300W into 4 ohms
Amplifier Power output Peak	1400 watt	
Standby Power Consumption	0.5 watt	120W Average, 800W Max
Headroom Limiter Maximizer	Yes	(Dynamic driver excursion control)
Auto Power detect on/off	Yes	
Finish	Satin	Black
Dimensions	H x W x D	32.8 x 20.3 x 18.1 in / 83.3 x 51.5 x 46.0 cm
Weight	Netto	134.7 lbs / 61.1 kg
Manual	Yes	Safety Manual included in packaging
Accesories	Yes	Gloves, US/EU Power cords, Rubber Feet
Version 1 - Dec 7th 2021		