

SDSP 1708/1712/1716/1724/1732

Multiswitch, Stand-alone

- ✓ Compact design
- ✓ Low Power Consumption
- ✓ Suitable for UHD
- ✓ Easy Installation



All devices have 16 active SAT IF inputs and one active terrestrial input.

Specifications						
		SDSP 1708	SDSP 1712	SDSP 1716	SDSP 1724	SDSP 1732
No. of inputs		16 x SAT, 1 x TERR				
No. of receiver outputs		8	12	16	24	32
Frequency range (MHz)	SAT	950 - 2150				
	TERR	47 - 862				
Gain (dB)	SAT	0 - 8	0 - 8	0 - 8	-3 - 6	-3 - 6
	TERR	-3 - 6	0 - 8	0 - 8	0 - 8	0 - 8
Isolation (dB)	TERR/SAT	30				
	SAT/TERR	28				
Cross polarisation isolation H/V (dB)		25				
Isolation (dB)	out - out TERR	22				
	out - out SAT	30				
Return-loss (dB)	SAT inputs	10				
	SAT outputs	8				
	TERR input	10				
	TERR outputs	8				
Output level (dBμV)	SAT (IMD3-35 dB)	100				
	TER (IMD3-60 dB)	88	88	88	83	83
Impedance (Ω)		75				
Switching signals		13 V/18 V, 13 V-22 kHz/18 V-22 kHz, DiSEqC 2.0				
Dimensions (mm)		147x203x50	187x203x50	227x203x50	307x203x50	387x203x50
Weight (g)		1400	1400	1400	1800	1800
Order No..		G.BB 82-00	G.BB 83-00	G.BB 84-00	G.BB 85-00	G.BB 86-00
EAN Code		40 45861 012713	40 45861 012720	40 45861 012737	40 45861 012744	40 45861 012751