

NWP222

Network in- & output panel - 2 x XLR in- & out + BT (4 x 2 (

Highlights:

- · 2 x XLR inputs & outputs
- Integrated Bluetooth receiver (Version 4.2)
- 4 x 4 channels Dante[™] & AES67
- Internal mixing & DSP
- · Ultra efficient cooling
- Superior sound quality & low latency

Product information:

The NWP222 is a Dante™/AES67 network input panel, featuring two XLR input and output connectors and an integrated Bluetooth receiver, which can be used to transmit or receive audio signals in a Dante™ audio network. The audio inputs can be switched between line-level and microphone-level audio signals and phantom power (+48 V DC) can be applied to the XLR input connectors for powering condenser microphones. Various further integrated functions such as integrated equalizing, automatic level control and other device settings can be configured through the AUDAC Touch™ app.

The front panel is finished with high-grade materials such as hardened glass makes them blend into any environment. These wall panels are compatible with standard EU-style in-wall boxes, these wall panels are the ideal solution for solid and hollow

The IP-based communication makes it future-proof while also being backwards compatible with many existing products. In contrast, the limited PoE power consumption makes it compatible with any PoE network-based installation.

Applications:

- Corporate
- Sporting facilities
- · Hotels
- Education
- · Government facilities
- Bars & Restaurants







Certification:

-‡ Dante - Dante



Properties:

(m) Internal mixing & EQ

Additional Inputs:

* Bluetooth

System specifications:

Inputs		2 x XLR female (in)
		2 x XLR male out
Control		2 buttons - Mic / Line switching
Indicators		2 LED's (RGB) - Input status
Configurable settings		IP settings
		Device name
		Input range (Mic / Line)
		Gain
		Phantom power
		DSP (EQ)
		Mixing
Configuration		Audac Touch™
Integrated DSP		Yes (EQ)
Automatic level control		Yes
Phantom power		+48 V DC
Power	Supply	PoE powered (IEEE 802.3at)
Connectors		XLR Female (mic in)
		RJ45 (network + PoE)
		1 x XLR male (audio out)

Product Features:

Construction	ABS	
Front finish	Elegant ABS front panel with glass	
Dimensions	160 x 88 mm (W x H) (Remote wall panel)	
Colours	White (RAL9003) (DWP240/W)	
	Black (RAL9005) (DWP240/B)	
Compatible devices	Any Dante™/AES67 compatible audio device	
Installation standard	Compatible with EU installation materials	

Variants:

- NWP222/B Black version
- NWP222/W White version

