

### Highlights:

---

- Stores up to 9 units of 19" Equipment
- Integrated ventilation grid on top
- Removable sides for easy installing & cabling
- Removable rear panel
- Punched square holes for use with snap-in cage nuts
- Front in depth adjustable 19" profiles (max 560 mm)
- Loading capacity of 60 kg
- Cable entry on top, back & bottom (closable)
- Tempered glass door with keylock
- Keylock with butterfly handle

### Product information:

---

The WPR609 is a professional 19" wall mount metal rack compliant to ANSI/EIA RS-310D, DIN41491, IEC 60297 standards. It is a solid construction with a cold-rolled steel 1,5 mm thick frame and 1,2 mm thick plates. The WPR609 comes fully assembled and can easily be mounted on the wall. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure easy fitting of the equipment.

The tempered smokey grey glass door is fitted with a key lock to keep the equipment only accessible for authorized persons. The removable sides and back panel allow easy installing and cabling of the equipment while the in depth adjustable 19" profiles provide great flexibility for installing equipment depending on its depth.



## Product Features:

---

Dimensions		600 x 501 x 600 mm (W x H x D)
Unit height		9 HE
Weight		27 kg
Colours		Black (RAL9004)
Max. load		60 kg
Max. usable depth		560 mm
Accessories	Included	10 x Cage nuts + screws
		2 x key for front door
		4 x Key for sidepanel lock
		1 x Allen key
		1 x WPR60LR
	Optional	KM600 - M6 Cage nuts
		KS600 - M6 x 16 mm bolt DIN7985 Black
		WPR10RF - Roof fan 120x120 mm
		SPR10DC - Dust cover brush
		WPR60FS - Fixed shelf

## Variants:

---

- WPR609R/B - Black version