

Product information:

CLV115 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. A aluminium foil shielding will grant with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected. On one side, the mini jack cable end is 15 cm (projector side) and on the other side (computer side) the mini jack cable end is 50 cm.

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- 7.5 mm (Ø) outer diameter
- Oxygen free copper
- Integrated stereo audio section
- Double Al-foil shielding

Components:

- CableType: SVGA215 - Audio + Video Cable



Properties:



Usage:

INSTALL

Physical Characteristics:

Inner conductor	Insulation	Material	FPE 1.55 mm (Ø)	
		Colours	White	
	Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap	
		Drain wire	BC 7 x 0.12 mm (Ø) (OFC)	
	Audio	Insulation	Material	PE 7540 0.7 mm (Ø)
			Colours	Grey / Purple
		Shielding	Spiral	CCA 28 x 0.12 mm (Ø)
Overall shielding	Aluminium foil			Al-mylar, 100% coverage - 25% Overlap
	Drain wire			BC 7 x 0.16 mm (Ø) (OFC)
Outer jacket	Material			PVC 7.5 mm (Ø)
	Colours			Black
Type of cable				75 Ω VGA video cable
Inner conductor	Material			BC 7 x 0.12 mm (Ø) (OFC)
	Audio	Material		BC 10 x 0.12 mm (Ø) (OFC)
Filling				Cotton Yarn
Inner conductor	American Wire Gauge			28 AWG
Fitted connectors				SVGA male

Variants:

- CLV115/1.5 - 1,5 meter
- CLV115/3 - 3 meter
- CLV115/5 - 5 meter
- CLV115/10 - 10 meter
- CLV115/15 - 15 meter
- CLV115/20 - 20 meter