

# WELL™ Fit



WELL™ Fit is a must for event lighting. A discrete, high powered LED up-lighter, this small battery powered wash light comes in a reflective chrome housing designed to blend into any décor. WELL™ Fit can be controlled wirelessly either by W-DMX or by an included IR remote; alternatively, it can be controlled manually from the OLED display on the fixture. All of these features combined make the WELL™ Fit a perfect solution for quick setup and distinguished accent lighting.

## FEATURES

- A completely wireless IP 65 rated battery powered up-light with four high powered quad colored RGBA LEDs that is controlled by W-DMX or IR remote.
- Chrome exterior for blending into its surroundings.
- Drop in case charging for easy storage and re-charging of the battery.
- 8 hours of operation at full and a quick 5 hours charging time for frequent use.
- Built in automated programs recallable by IR, WDMX or manually.
- Built in kickstand for positioning light where you need it.
- M12 threaded insert for easy clamp installation and a Kensington lock position for securing your investment.

## PRELIMINARY SPECIFICATIONS

### Optical

- Light Source: 4 LEDs (quad- color RGBA) 10 W, (720 mA), 50,000 hours life expectancy).
- Beam Angle: 11°
- Field Angle: 18°
- Illuminance (18°): 800 lux @ 5 m

### Dynamic Effects

- Color Macros: 5 macros
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 24 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

### Construction/Physical

- Dimensions: 5.4 x 5.7 x 8 in (138 x 145 x 202 mm)
- Dimensions (charging case): 20.4 x 18.5 x 21.2 in (519 x 470 x 540 mm)
- Weight (single unit) 7.4 LB (3.4 kg)
- Weight (charging case): 103.6 lb (47 kg)
- Exterior Color: Chrome
- Housing Material: Aluminum die-cast

### Connections

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Cable Length (power): 5 ft (1.5 m)

### Control

- Control Protocol: W-DMX, IRC
- DMX Channels: 3, 4, 6 or 10
- Modes/Personalities: 5 personalities (4Ch, 6Ch, 10Ch, HSV, HSI)

# Ovation™ Min-E-10CW

## PRELIMINARY SPECIFICATIONS (CONTINUED)

### Certifications/Qualifications

- CE, MET
- IP Rating: IP20, dry location

### What's Included

- Ovation Min-E-10CW
- Gobo holder size E: 37.5 mm (outside), 28 mm (image), 1 mm (max. thickness)
- Gel frame (2.75 in/70 mm accessories)

### Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Color Blending Filters: DF60X1D, DF20D

