

OHA 110
OHA 115
OHA 120
OHA 125

1-fach-Abzweiger horizontal

- ◆ Frequenzbereich 5...2400 MHz
- ◆ Rückkanaltauglich
- ◆ Massives, korrosionsfestes Druckgussgehäuse
- ◆ Befestigungslöcher für Aufputzmontage
- ◆ F-Anschlüsse

■ KLASSE
A
■ CLASS



Typ	OHA 110	OHA 115	OHA 120	OHA 125
Art.-Nr.	22510149	22510150	22510151	22510152
Abzweigdämpfung (dB)				
5...1000 MHz	10,0 ± 1,0	15,0 ± 1,0	20,0 ± 1,0	25,0 ± 1,0
1000...2400 MHz	10,0 ± 1,5	15,0 ± 1,5	20,0 ± 1,5	25,0 ± 1,5
Durchgangsdämpfung (dB)				
5...40 MHz	2,0	1,0	1,0	1,0
40...1000 MHz	2,5	2,0	1,5	1,5
1000...2400 MHz	3,5	2,5	2,0	2,0
Rückflussdämpfung (dB)				
5...40 MHz	14,0	16,0	18,0	18,0
40...1000 MHz	14,0	14,0	14,0	14,0
1000...2400 MHz	12,0	12,0	12,0	12,0
Schirmungsmaß (dB)				
40...470 MHz	>75	>75	>75	>75
470...1000 MHz	>65	>65	>65	>65
1000...2400 MHz	>55	>55	>55	>55