

Datum: June 4, 2009 1

Universal-Antennensteckdose für CATV, SAT und Für alle Unicable-Systeme nach EN50494

	SSD 5-00	SSD 5-10	SSD 5-14	SSD 5-18
Frequency range SAT	950 –2200 MHz			
Frequency range TV	5-65 MHz / 125 –862 MHz			
Frequency range RADIO	87,5 –108 MHz			
Through loss (dB)				
SAT	-	≤ 4,5 dB	≤ 3,5 dB	≤ 3,0 dB
TV	-	≤ 2,5 dB	≤ 2,0 dB	≤ 2,0 dB
RADIO	-	≤ 2,0 dB	≤ 1,5 dB	≤ 1,5 dB
Tap loss				
SAT	≤ 3,0 dB	10 dB	14 dB	18 dB
TV	≤ 2,0 dB	10 dB	14 dB	18 dB
RADIO	≤ 4,5 dB	14 dB	18 dB	22 dB
Returnn loss				
Input	≥ 14dB ¹⁾	≥ 18dB ²⁾		
Output	-	≥ 18dB ²⁾		
SAT	≥ 10dB ¹⁾	≥ 10dB ²⁾		
TV	≥ 14dB ¹⁾	≥ 14dB ²⁾		
Radio	≥ 10dB ¹⁾	≥ 10dB ²⁾		
Connectoer SAT	F-female			
Connector TV	IEC-male			
Connector Radio	IEC-female			
Screening	Class A			

¹⁾ Tabelle 1 according EN 60728-4

²⁾ Tabelle 2 according EN 60728-4
(typische Werte)